

**MW SERIES CHILLER SYSTEMS  
3 HP TO 24 HP PACKAGED WATER COOLED**

**SINGLE COMPRESSOR SYSTEMS**

DESCRIPTION	MODEL	BTU/HR*	PROCESS PUMP	TANK CAPACITY (GAL)	DIMENSIONS L X W X H (INCHES)	SHIP WEIGHT (LBS)
3 HP WATER COOLED CHILLER SYSTEM	PMW3F1H22	23,200	.75 HP	70 GAL	57 X 43 X 68	1,100
5 HP WATER COOLED CHILLER SYSTEM	PMW5F1H22	37,500	1 HP	70 GAL	57 X 43 X 68	1,300
7.5 HP WATER COOLED CHILLER SYSTEM	PMW7.5F2H22	55,000	1 HP	70 GAL	57 X 43 X 68	1,580
10 HP WATER COOLED CHILLER SYSTEM	PMW10F2H22	73,900	1.5 HP	70 GAL	57 X 43 X 68	1,625
12 HP WATER COOLED CHILLER SYSTEM	PMW12F3H22	92,800	1.5 HP	70 GAL	57 X 43 X 68	1,800

**DUAL COMPRESSOR SYSTEMS**

DESCRIPTION	MODEL	BTU/HR*	PROCESS PUMP	TANK CAPACITY (GAL)	DIMENSIONS L X W X H (INCHES)	SHIP WEIGHT (LBS)
6 HP WATER COOLED CHILLER SYSTEM	PMW2/3F2H22	46,400	1 HP	142 GAL	90 X 43 X 64	1,480
10 HP WATER COOLED CHILLER SYSTEM	PMW2/5F2H22	75,000	1.5 HP	142 GAL	90 X 43 X 64	1,825
15 HP WATER COOLED CHILLER SYSTEM	PMW2/7.5F4H22	110,000	2 HP	142 GAL	90 X 43 X 64	2,200
20 HP WATER COOLED CHILLER SYSTEM	PMW2/10F4H22	147,800	2 HP	142 GAL	90 X 43 X 64	2,380
24 HP WATER COOLED CHILLER SYSTEM	PMW2/12F6H22	185,600	2 HP	142 GAL	90 X 43 X 64	2,550

\* Capacity based on 33 F Glycol and 110 F Cond. Temperature

**MW SERIES SYSTEMS ARE SUPPLIED STANDARD WITH:**

- BRUSHED ALUMINUM SERVICE PANELS
- DIGITAL GLYCOL TEMPERATURE DISPLAY
- MAIN ELECTRICAL DISCONNECT
- COAXIAL WATER COOLED CONDENSERS
- WATER REGULATING VALVES
- REFRIGERANT GAUGES

